Electric Thermostat Water Bath LX10TWB

Email: info@labdex.com **website:** www.labdex.com

Description

This has a novel and beautiful appearance designed with microcomputer program controller system. Equipped with a menu-type operation interface it can also simplify the complex experimental process. It has an over-temperature sound and light tracking alarm system to reliably protect the sample.

Specifications

Volume	11 L
Temperature control range	RT+5~100℃
Temperature fluctuation degree	±0.5℃
Temperature resolution ratio	0.1℃
Power	600 W
Inner dimensions	420 x 180 x 150
Overall dimensions	490 x 250 x 330 mm
Net weight	8 kg
Packing dimensions	570 x 340 x 370 mm
Gross weight	10 kg

Features

- Microcomputer program controller, time and heating rate
- Digital display of actual temperature and set temperature
- Over temperature sound and light tracking alarm function
- Simplify the complex experimental process
- Realize automatic control
- Conduct constant temperature tests at a very fast speed

Applications

- Used for precision constant temperature and auxiliary heating in industries, mining enterprises, scientific research and in colleges and universities.

Optional Accessories

- Multi-segment programmable controller

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com